

Product information | TECHNICAL DATA SHEET

1K HS CLEAR COAT

400ml Net

GENERAL DESCRIPTION

BPS 1K HS CLEAR COAT is a high solids clear coat, made with solvent-based thermoplastic acrylic resins. Ultra-fast drying, its main function is to protect and protect different surfaces, 1K HS Clear is perfect for refinishing small accessories, door jambs ,underhoods,inner panels and new part cut-ins.

CHARACTERISTICS

- Very fast drying
- High gloss finish
- Save time and material
- Reduces repair time and steps to maximize shop efficiency
- Excellent adhesion
- High durability
- Easy to apply and re-coat
- Good water resistant
- Good resistance to UV light

APPLICATION

Suitable in the automotive industry, especially as a clear protective layer on automotive paint surfaces, vehicle body refinishing as well as general painted metal, plastic, aluminium and alloy surfaces.

INSTRUCTIONS FOR USE:

- Shake can well for one minute
- Use outdoors or in a well-ventilated area.
- Avoid use in windy conditions.
- Cover surrounding area to protect from over-spray.
- Ideal application temperature between 10°C and 35°C
- Safety data sheets are available.

CLEAN-UP: When finished spraying, reverse spray for 2-3 seconds and wipe

off tip before storing. Clean up wet paint with suitable thinners or spirits.

Discard empty container.Do not burn or place in home trash bin.

CLOGGING: If it is clogged and cannot be sprayed, it is recommended to replace the nozzle, or flush the nozzle with solvent such as mineral spirits. Do not stick pin or other object into the stem.

TECHNICAL PROPERTIES

1K HS CLEAR COAT	
Paint Film Appearance	Clear
Resin Type	Acrylic
Product Type	Solvent-based
Pigment Type	—
Fill Weight	240g
Drying time (23°C and 50% R.H)	Approx. 10 min (Touch)
	1 hours (Handle)
	Within 5min (Recoat)
Inner Pressure	0.42±0.10 MPa
Leak Test	No leakage
Spray Rate	≥97%
Temperature Resistance	Up to 80°C
Shelf Life	3 years

STORAGE AND SHELF LIFE

3 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60% .

WARNINGS

Keep out of reach of children. Contents under pressure. Do not puncture or incinerate container.

Do not expose to heat or store at temperature above 50°C. Avoid freezing.



IMAGE



Dia 65 mm x198mm total Height

LABEL



CAP SYSTEM



Clear

Transversal Cap

PACKAGING

Capacity 400 ml.

Packaging heat resistance: <50°C

Brown Box (12 units)

270 X 205 X 205 mm

