

Product information | TECHNICAL DATA SHEET

2K HS CLEAR COAT

400ml Net

GENERAL DESCRIPTION

Professional 2K high solids clear coat delivering exceptional gloss for premium automotive refinishing.

CHARACTERISTICS

- High solids (HS) formula
- Two component (2K) activated
- Outstanding gloss and gloss retention
- Excellent scratch and abrasion resistance
- Superior resistance to fuels, chemicals and weathering
- Excellent UV resistance
- Fast-drying, durable finish
- Professional trade-quality

APPLICATION

Ideal for automotive refinishing and surface repair. Applied as high gloss clear top coat on all car body painted surfaces

-Full panel repairs • Automotive refinishing • Spot repairs • Vehicle bodywork • Motorcycles • Automotive accessories • Metal surfaces

INSTRUCTIONS FOR USE:

-Activate internal hardener by removing yellow cap from clear lid and inserting into the bottom of can. Then shake can well for 1-2 minutes.

Use outdoors or in a well-ventilated area.

- Avoid use in windy conditions.
- Cover surrounding area to protect from over-spray.
- Ideal application temperature between 10°C and 35°C

Safety data sheets are available.

CLEAN-UP: When finished spraying, reverse spray for 2-3 seconds and wipe off tip before storing. Clean up wet paint with suitable thinners or spirits.

Discard empty container. Do not burn or place in home trash bin.

CLOGGING: If it is clogged and cannot be sprayed, it is recommended to replace the nozzle, or flush the nozzle with solvent such as mineral spirits. Do not stick pin or other object into the stem.

2K CLEAR COAT	
Paint Film Appearance	Flat and smooth
Resin Type	Acrylic
Product Type	Solvent-based
Pigment Type	Transparent
Fill Weight	240g
Drying time (23°C and 50% R.H)	Approx. 10 min (Touch) 1 hours (Handle) Within 5min (Recoat)
Inner Pressure	0.42±0.10 MPa
Leak Test	No leakage
Spray Rate	≥97%
Temperature Resistance	Up to 80°C
Shelf Life	3 years

STORAGE AND SHELF LIFE

3 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60% .

WARNINGS

Keep out of reach of children. Contents under pressure. Do not puncture or incinerate container.

Do not expose to heat or store at temperature above 50°C. Avoid freezing.



IMAGE



Dia 65 mm x198mm total Height

LABEL



CAP SYSTEM



Transversal Cap

Clear

PACKAGING

Capacity 400 ml.
Packaging heat resistance: <50°C
Brown Box (12 units)
270 X 205 X 205 mm

