

Product information | TECHNICAL DATA SHEET

ACRYLIC SPRAY PAINT

400ml Net

GENERAL DESCRIPTION

BPS Acrylic Spray Paint is made from thermoplastic acrylic resin spray paint and it can be applied by aerosol spray and provide films with excellent performance such as excellent weather resistance, good leveling, strong coverage, fast dry, high build, and match well with many types of primers.

CHARACTERISTICS

- Fast drying and simple operation
- Good spray atomization
- High spray rate
- High film fullness
- Excellent decorative effect
- Superior adhesion and durability
- Indoor/outdoor use with maximum rust protection
- No sanding or priming required
- Fade and chip resistant
- Excellent protection against impact, UV, etc.

APPLICATION

Suitable as for spraying, refinishing and decoration on metal, wood and plastic surfaces. and especially for metal surface repairing.

- Metal surface
- Industry
- Wood
- DIY
- Maintenance

INSTRUCTIONS FOR USE:

- Before use, shake the can very well for about a minute after hearing the noise of the mixing ball. Surface should be clean, dry and free from potential contaminants such as oil, dirt, grease or rust
- Use outdoors or in a well-ventilated area.
- Avoid use in windy conditions.
- Cover surrounding area to protect from overspray.
- Ideal application temperature between 10°C and 35°C.
- Safety data sheets are available.

TECHNICAL PROPERTIES

SPRAY PAINT(ACRYLIC)	
Paint Film Appearance	Uniform color, flat and smooth
Resin Type	Acrylic
Product Type	Solvent-based
Pigment Type	Varies with color
Fill Weight	240g
Drying time (23°C and 50% R.H)	Approx. 5 min (Touch) 1 hours (Handle) Within 5min (Recoat)
Inner Pressure	0.42±0.10 MPa
Leak Test	No leakage
Spray Rate	≥97%
Temperature Resistance	Up to 80°C
Shelf Life	3 years

Notes: Conditioning, specimen is conditioned under (23±2) °C, (50±5)% relative humidity if not specified; Testing Condition, specimen is tested at (23±2) °C, (50±5)% relative humidity

if not specified; The above data is intended to provide guidance for use and should not be Used to write product specifications.

STORAGE AND SHELF LIFE

3 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60% .

WARNINGS

Keep out of reach of children. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperature above 50 °C. Avoid freezing.



IMAGE



Dia 65 mm x198mm total Height

LABEL



CAP SYSTEM



Transversal Cap

RAL9005-Matt Black

PACKAGING

Capacity 400 ml.
Packaging heat resistance: <50°C
Brown Box (12 units)
270 X 205 X 205 mm

