

Product information | TECHNICAL DATA SHEET

ADHESION PROMOTER

400ml Net



GENERAL DESCRIPTION

BPS Special adhesion promoter for pre-treating paintable hard plastics or standard plastic parts, indoors and outdoors. The light pigmentation indicates, where the spray has already been applied. For perfect adhesion to plastic.

CHARACTERISTICS

- Special primer for plastics with good adhesion properties
- For all paint-able hard plastics
- Check plastic surfaces for compatibility

Weather resistant, for indoors and outdoors

APPLICATION

It mainly used for automotive plastic parts, car bumper and plastic surface painting. Greatly improve paint adhesion, avoid paint peeling and falling off.

- Automotive
- Plastic surface
- Metal surface
- Fibreglass
- DIY
- Maintenance

INSTRUCTIONS FOR USE:

- Before use, shake the can very well for about a minute after hearing the noise of the mixing ball.
- Clear fast-drying primer for plastics, metals and fibreglass surface, ready in 3-5 minutes to top coat.
- Use outdoors or in a well-ventilated area.
- Avoid use in windy conditions.
- Cover surrounding area to protect from over-spray.
- Ideal application temperature between 10°C and 35°C.
- Safety data sheets are available.

CLEAN-UP: When finished spraying, reverse spray for 2-3 seconds and wipe off tip before storing. Clean up wet paint with suitable thinners or spirits.

Discard empty container. Do not burn or place in home trash bin.

CLOGGING: If it is clogged and cannot be sprayed, it is recommended to replace the nozzle, or flush the nozzle with solvent such as mineral spirits. Do not stick pin or other object into the stem.

TECHNICAL PROPERTIES

PLASTIC ADHESION PRIMER	
Paint Film Appearance	Uniform color, flat and smooth
Resin Type	Acrylic
Product Type	Solvent-based
Fill Weight	240g
Drying time (23°C and 50% R.H)	Approx. 5 min (Touch)
	1 hours (Handle)
	Within 5min (topcoat)
Inner Pressure	0.42±0.10 MPa
Leak Test	No leakage
Spray Rate	≥95%
Temperature Resistance	Up to 80°C
Shelf Life	3 years

STORAGE AND SHELF LIFE

3 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).

WARNINGS

Keep out of reach of children. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperature above 50 °C. Avoid freezing.

IMAGE



Dia 65 mm x198mm total Height

LABEL



CLEAR

CAP SYSTEM



transversal Cap

PACKAGING

Capacity 400 ml.

Packaging heat resistance: <50°C

Brown Box (12 units)

270 X 205 X 205 mm

