

ETCH PRIMER

400ml Net

**GENERAL DESCRIPTION**

BPS Self etching primer prepares bare metal, aluminum and fiberglass surfaces to promote maximum adhesion and smoothness of the top coat. This product is formulated to stop rust and is an essential step to achieve a professionally finished product.

CHARACTERISTICS

- Etch and primes bare metals, aluminium and fibreglass.
- Formulated to stop rust.
- Use outdoors or in a well-ventilated area.
- Avoid use in windy conditions.
- Cover surrounding area to protect from overspray.
- Ideal application temperature between 10°C and 35°C.

APPLICATION

Suitable for bare metal, aluminium and fiberglass surfaces to promote maximum adhesion and smoothness for top coats

- Automotive
- bare metal
- Aluminium
- Fibreglass
- DIY
- fabrications

INSTRUCTIONS FOR USE:

- Before use, shake the can very well for about a minute after hearing the noise of the mixing ball.
- Clean the area to be painted with mineral spirits to remove all oil, grease, wax, and dirt.
- Dry thoroughly. Remove loose paint and rust with a wire brush or sandpaper.
- Clean the surface with a commercial detergent, or other suitable cleaning method.
- Rinse with fresh water and allow to thoroughly dry. Lightly sand glossy surfaces.
- Do not apply to equipment connected to the mains and use in well ventilated areas.
- Safety data sheets are available.

CLEAN-UP: When finished spraying, reverse spray for 2-3 seconds and wipe off tip before storing. Clean up wet paint with suitable thinners or spirits.

Discard empty container. Do not burn or place in home trash bin.

CLOGGING: If it is clogged and cannot be sprayed, it is recommended to replace the nozzle, or flush the nozzle with solvent such as mineral spirits. Do not stick pin or other object into the stem.

TECHNICAL PROPERTIES

SELF ETCHING PRIMER	
Paint Film Appearance	Uniform color, flat and smooth
Resin Type	Acrylic
Product Type	Solvent-based
Pigment Type	Varies with color
Fill Weight	240g
Drying time (23°C and 50% R.H)	Approx. 5 min (Touch) 1 hours (Handle) Within 5min (Recoat) Top coat 20 minutes
Inner Pressure	0.42±0.10 MPa
Leak Test	No leakage
Spray Rate	≥97%
Temperature Resistance	Up to 80°C
Shelf Life	3 years

STORAGE AND SHELF LIFE

3 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).

WARNINGS

Keep out of reach of children. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperature above 50 °C. Avoid freezing.

IMAGE

Dia 65 mm x198mm total Height

LABEL

Grey

CAP SYSTEM

transversal Cap

PACKAGING

Capacity 400 ml.
Packaging heat resistance: <50°C
Brown Box (12 units)
270 X 205 X 205 mm

