



Product information | TECHNICAL DATA SHEET

STONE GUARD

400ml Net

GENERAL DESCRIPTION

A paintable undercoating for all vehicle undercarriages. Forms a rubberized skin that reduces road noise and protects metal from salt corrosion and road debris.

Dries fast and does not sag. Does not "bleed-thru" when top-coated.

CHARACTERISTICS

- Rubberized formula for maximum protection against rust.
- Provides excellent sound dampening
- Seals out water, fumes, road chemicals and dust
- Ideal for auto panels, fenders, hoods, truck interiors and all chassis parts

APPLICATION

Suitable as the automotive industry and especially for all vehicle undercarriages

- Automotive
- Industrial
- All vehicle undercarriages.
- DIY
- Maintenance

INSTRUCTIONS FOR USE:

-Surface should be clean, dry and free from potential contaminants such as oil, dirt, grease or rust.

- Textured rubberized stone guard coating.

- Designed to protect against stone chips, salt, moisture and rust.

-Use outdoors in a well-ventilated area.

-Avoid use in windy conditions.

-Cover surrounding area to protect from overspray.

-Ideal application temperature between 10°C and 35°C

- Safety data sheets are available.

TECHNICAL PROPERTIES

STONE GUARD	
Paint Film Appearance	Textured
Resin Type	Rubberized
Product Type	Solvent-based
Pigment Type	Black
Fill Weight	480g
Drying time (23°C and 50% R.H)	Approx. 15 min (Touch) 2 hours (Handle) 24 hour (dry time) Within 5min (Recoat)
Inner Pressure	0.42±0.10 MPa
Leak Test	No leakage
Spray Rate	≥95%
Temperature Resistance	Up to 80°C
Shelf Life	3 years

Notes: Conditioning, specimen is conditioned under (23±2) °C, (50±5)% relative humidity if not specified; Testing Condition, specimen is tested at (23±2) °C, (50±5) relative humidity

if not specified; The above data is intended to provide guidance for use and should not be Used to write product specifications.

STORAGE AND SHELF LIFE

3 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60% .

WARNINGS

Keep out of reach of children. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperature above 50 °C. Avoid freezing.

IMAGE



Dia 65 mm x198mm total Height

LABEL



CAP SYSTEM



Black

Transversal Cap

PACKAGING

Capacity 400 ml.

Packaging heat resistance: <50°C

Brown Box (12 units)

270 X 205 X 205 mm

